









Sullivan Gulch Drill Hole IDM18-059: Idealized East-West Cross Section



2.53 g/t AuEq over 109.73 m
(1.71 g/t Au and 69.03 g/t Ag)

Mineralized Zone

Including 4.11 g/t AuEq over 21.34 m
(1.93 g/t Au and 185.24 g/t Ag)

-  Drill Trace
-  Banded Rhyolite
-  Porphyritic Rhyolite
-  Quartz Latite
-  Porphyritic Latite
-  Basalt
-  Planned Q1 2019 In-fill and Step-Out Drilling

0 m 200 m

1. Downhole thickness; true width varies depending on drill hole dip; most drill holes are aimed at intersecting the vein structures close to perpendicular therefore true widths are close to downhole widths (approximately 75% conversion ratio)
 2. Gold equivalent = g Au/t + (g Ag/t * 85)
 3. Thorough QA/QC protocols are followed on the Project, including insertion of duplicate, blank and standard samples in the assay stream for all drill holes. The samples are submitted directly to American Assay Labs in Reno, Nevada for preparation and analysis. Analysis of gold is performed using fire assay method with atomic absorption (AA) finish on a 1 assay ton aliquot. Gold results over 5 g/t are re-run using a gravimetric finish. Silver analysis is performed using ICP for results up to 100 g/t on a 5 acid digestion, with a fire assay, gravimetric finish for results over 100 g/t silver.